

INSTALLATION INSTRUCTIONS



©2021

SnapWrap Hanger

1861 IB A

PRODUCT DESCRIPTION

SnapWrap Hanger is the most effective way to manage multiple cables in a single universal wrapping strap. These straps can replace traditional hangers and endless combinations of multi-cable cushions. SnapWrap hangers are optimized to reduce PIM while maximizing structural integrity.

TYPICAL APPLICATIONS

Strap with strap tensoning corrugations for different bundle sizes

Strap clips

Latches

1

Hold the Snapwrap with the "CABLE BUNDLE THIS SIDE" facing up and place the cables that you want to secure on top of the strap near the edge with the latches.

2

Stretch and wrap strap tightly around cable bundle expanding the corrugations until you get two strap holes to slide down onto the latches.

3

Snap hanger into 3/4" hole.

4

Secure excess strap onto itself using strap clips. Installation is complete as shown.

5

To remove: Press down with thumb and apply pressure with fingers on clip to squeeze latches together and rotate hanger out.

Minimum cable and cable bundle size 1/2" (13mm)

Maximum cable and cable bundle size 2" (51mm)

Additional PIM-Free Adapters

Part Number	Description
UA-3C	PIM free angle adapter
SA-3C	PIM free round member adapter
SA-1TR	PIM free multifunction adapter