



Radio Frequency Systems line of high performance coaxial cable connectors are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up the attachment of connectors to Air Dielectric Cable® coaxial cables. RFS Technologies connectors are fully tested for mechanical and electrical compliance specifications. They are available in all popular cable sizes in a variety of mating interfaces. To join two cables with EIA connectors, two identical socket connectors are installed on either end of the cables to be joined, and a coupling element is used to make the connection of the center conductor. The coupling element must be ordered separately with the exception of the S-Line male versions that have a captivated coupling element. Connectors are available in sizes matching the nominal cable size. EIA connectors provide optimal power handling for the complete transmission line system.;

FEATURES / BENEFITS

- Solderless - Captivated spring finger contacts permit quick, easy and precise solderless installation utilizing only basic hand tools. Avoids the high impedance risk associated with soldering.
- Self Flaring - Self flaring design reduces installation time and thus, saves on labor costs.
- Corrosion-Proof Silver Plated Contacts - Featured even on standard connectors. Provide improved contact resistance and lower intermodulation.
- Outstanding Electrical Performance - Metal to Metal contact between cable and connector - no plastic parts used. Secure connection highly resistant to pull-off or twist-off provides long-term mechanical integrity. Resistant to intermodulation after temperature cycling.
- Easy to Install - No special tools needed. Only basic hand tools required. No additional costs to the installer.

Technical features

GENERAL SPECIFICATIONS

Transmission Line Type		Coaxial Cable
Cable Size		2-1/4
Cable Type		Air Dielectric
Model Series		HCA214-50 Series
Connector Interface		3-1/8" EIA
Connector Type		Gas Barrier
Sealing Method		O-ring
Gender		None

MECHANICAL SPECIFICATIONS

Plating Outer/Inner		Brass/Silver
Length	mm (in)	127 (5)
Outer Diameter	mm (in)	136.8 (5.2)
Inner Contact Attachment		Threaded
Outer Contact Attachment		Tab Flare

ACCESSORIES

Wrench size front	mm (in)	67 (2-5/8)
Wrench size rear	mm (in)	67 (2-5/8)

[External Document Links](#)
[Installation Instruction](#)

[Notes](#)