



**43F-LCF114-E01**

**4.3-10 Female Straight Connector for 1 1/4" Coaxial Cable, OMNI FIT™ Premium, O-Ring and compression sealing**

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminium) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS Technologies connectors are fully tested for mechanical and electrical compliance to industry specifications.

The 4.3-10 connector is an innovative, space-saving RF connection meeting all requirements even under the most severe environmental conditions and not relying on coupling nut torque. Sealing against outer conductor and jacket by means of the o-ring and 360° compression fit.

Multifunctional, self-lubricating HighTech polymer assembly locks on cable corrugation, avoids electrochemical potential differences and compression-fits to the jacket.

**FEATURES / BENEFITS**

- Ultra high PIM performance i.e. reduced interference leading to high customer satisfaction
- Two-piece design i.e. visual inspection of interlocking leads to improved installation security
- OMNI FIT™ concept i.e. streamlined order management and reduced stock level
- Watertight sealing in mated and unmated condition, i.e. reduced efforts during installation and improved security during operation
- Tri metal alloy plating i.e. extreme resistance against corrosion even under hardest climatic and environmental circumstances
- Multi-thread (Tristart) design i.e. simplified and accelerated tightening process
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



**Technical features**

**GENERAL SPECIFICATIONS**

<b>Transmission Line Type</b>		Coaxial Cable
<b>Cable Size</b>		1 1/4
<b>Cable Type</b>		Foam Dielectric
<b>Connector Interface</b>		4.3-10
<b>Connector Type</b>		OMNI FIT™ PREMIUM Straight
<b>Sealing Method</b>		Sealing Rubber + 360° Clamping
<b>Gender</b>		Female

**ELECTRICAL SPECIFICATIONS**

<b>Nominal Impedance, ohms</b>	Ohm	50
<b>3rd Order IM Product @ 2x20 Watts</b>	dBc	-163 ; typical -167
<b>Maximum Frequency</b>	GHz	6.0
<b>VSWR, Return Loss</b>	VSWR (dB)	0 &lt; f ≤ 1.0 GHz: 1.02 (40) 1.0 &lt; f ≤ 2.2 GHz: 1.04 (34) 2.2 &lt; f ≤ 2.7 GHz: 1.06 (31) 2.7 &lt; f ≤ 3.6 GHz: 1.08 (28)



**43F-LCF114-E01**

4.3-10 Female Straight Connector for 1 1/4" Coaxial Cable, OMNI FIT™ Premium, O-Ring and compression sealing

**MECHANICAL SPECIFICATIONS**

<b>Plating Outer/Inner</b>		Tri metal alloy / Silver
<b>Length</b>	mm (in)	82.55 (3.25)
<b>Outer Diameter</b>	mm (in)	50.95 (2)
<b>Inner Contact Attachment</b>		Basket
<b>Outer Contact Attachment</b>		360° clamping

**ACCESSORIES**

<b>Wrench size front</b>	mm (in)	48
<b>Wrench size rear</b>	mm (in)	48

**TESTING AND ENVIRONMENTAL**

<b>Waterproof Level</b>		IP68
-------------------------	--	------

[External Document Links](#)  
[Installation Instruction](#)

[Notes](#)