

4.3-10 Female Connector for 1/2" Coaxial Cable, OMNI FIT™ standard, O-ring sealing

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector- cable interface while simplifying and speeding up connector attachment. The 4.3-10 connector is an innovative, space-saving RF connection meeting all requirements even under the most severe environmental conditions and not relying on coupling nut torque to meet PIM performance.

FEATURES / BENEFITS

- Cost effective two-piece design for safe and easy installation
- Compatible with copper and aluminium cable types i.e. one connector for both outer conductor materials eliminates the risk of faulty connector installation and helps to keep inventory down
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up reduces the number of dropped calls and avoids revenue losses
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



43F-LCF12-C03

Technical features

GENERAL SPECIFICATIONS

Transmission Line Type	Coaxial Cable		
Cable Size	1/2		
Cable Type	Foam Dielectric		
Model Series	LCF12-50 Series	ICA12-50 Series	RCF12-50 Series
Connector Interface	4.3-10		
Connector Type	OMNI FIT™ Standard		
Sealing Method	O-ring		
Gender	Female		

ELECTRICAL SPECIFICATIONS

Nominal Impedance, ohms	Ohm	50
3rd Order IM Product @ 2x20 Watts	dBc	-162 ; typical -166
Maximum Frequency	GHz	6.0
VSWR, Return Loss	VSWR (dB)	0 < $f \le 1.0$ GHz: 1.03 (36.6) 1.0 < $f \le 2.7$ GHz: 1.04 (34.1) 2.7 < $f \le 3.7$ GHz: 1.08 (28.3) 3.7 < $f \le 5.0$ GHz: 1.10 (26.4) 5.0 < $f \le 6.0$ GHz: 1.25 (19.1)

MECHANICAL SPECIFICATIONS

Plating Outer/Inner		Trimetal/Silver
Length	mm (in)	54.2 (2.13)
Outer Diameter	mm (in)	22 (0.87)
Inner Contact Attachment		Spring Finger
Outer Contact Attachment		Spring C-Ring

43F-LCF12-C03 REV : E REV DATE : 14 Oct 2025 www.rfstechnologies.com



4.3-10 Female Connector for 1/2" Coaxial Cable, OMNI FIT™ standard, O-ring sealing

ACCESSORIES Wrench size front mm (in) 20 (13/16) Wrench size rear 20 (13/16) mm (in) **Trimming Tool** TRIM-SET-L12-C02 **TESTING AND ENVIRONMENTAL Waterproof Level** IP68 54.2 REF S20.0Marker S20.043F-LCF12-C03 Outline Drawing **External Document Links** Notes

Installation instruction

www.rfstechnologies.com REV: E REV DATE: 14 Oct 2025 43F-LCF12-C03