



OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS Technologies connectors are fully tested for mechanical and electrical compliance to industry specifications.

The 7-16 connector is the most rugged RF connection meeting all requirements even under the most severe environmental conditions.

**FEATURES / BENEFITS**

- Cost effective two-piece design for safe and easy installation
- Compatible with copper and aluminium cable types i.e. one connector for both outer conductor materials eliminates the risk of faulty connector installation and helps to keep inventory down
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up reduces the number of dropped calls and avoids revenue losses
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



OMNI FIT™ Standard Connectors

**Technical features**

**GENERAL SPECIFICATIONS**

<b>Transmission Line Type</b>		Coaxial Cable	
<b>Cable Size</b>		1 5/8	
<b>Cable Type</b>		Foam Dielectric	Radiating
<b>Model Series</b>		LCF158-50 Series	RCF158-50 Series
<b>Connector Interface</b>		7-16 DIN	
<b>Connector Type</b>		OMNI FIT™ Standard	
<b>Sealing Method</b>		O-ring	
<b>Gender</b>		Female	

**ELECTRICAL SPECIFICATIONS**

<b>Nominal Impedance, ohms</b>	Ohm	50
<b>3rd Order IM Product @ 2x20 Watts</b>	dBc	-159 typical
<b>Maximum Frequency</b>	GHz	2.75
<b>VSWR, Return Loss</b>	VSWR (dB)	0 <math>\leq f=1.0\text{ GHz}</math>: 1.03 (36.6) 1.0 <math>\leq f=2.2\text{ GHz}</math>: 1.04 (34.1)

**MECHANICAL SPECIFICATIONS**

<b>Plating Outer/Inner</b>		Trimetal/Silver
<b>Length</b>	mm (in)	64.6 (2.54)
<b>Outer Diameter</b>	mm (in)	62.9 (2.5)
<b>Inner Contact Attachment</b>		Spring Finger
<b>Outer Contact Attachment</b>		Spring C-Ring



### 716F-LCF158-C02


7-16 DIN Female Connector for 1-5/8" Coaxial Cable, OMNI FIT™ standard, O-ring sealing

#### ACCESSORIES

<b>Wrench size front</b>	mm (in)	Open end wrench 55 (2-1/6)
<b>Wrench size rear</b>	mm (in)	Open end wrench 60 (2-1/3)
<b>Poly Hook Spanner</b>	mm (in)	PHS 60-90-5 Ø 60-90 (2.3-3.5) Pin 5 (0.2)

#### TESTING AND ENVIRONMENTAL

<b>Waterproof Level</b>		IP68
-------------------------	--	------



- [External Document Links](#)
- [Application Note](#)
- [Installation Instruction](#)

[Notes](#)