




**716F-NXM**

Coaxial Adapter 7-16 Female to NEX10 Male

Coaxial Adapter, 7-16 Female / NEX10 Male

FEATURES / BENEFITS



External Document Links

Notes

**Technical features**

**STRUCTURE**

|              |  |                          |
|--------------|--|--------------------------|
| Product Line |  | Coaxial Cable Components |
| Product Type |  | Coaxial Adapter          |

**MECHANICAL SPECIFICATIONS**

|                            |  |                         |
|----------------------------|--|-------------------------|
| Connector A                |  | 7-16 Female             |
| Center Contact Connector A |  | Copper, silver plated   |
| Outer Contact Connector A  |  | Copper, Tin-Zinc plated |
| Connector B                |  | NEX10 Male              |
| Center Contact Connector B |  | Copper, silver plated   |
| Outer Contact Connector B  |  | Copper, Tin-Zinc plated |
| Dielectric                 |  | PTFE                    |
| Sealing class              |  | IP68, connected         |

**ELECTRICAL SPECIFICATIONS**

|                                   |           |                              |
|-----------------------------------|-----------|------------------------------|
| Frequency Range - MHz             |           | DC - 6000                    |
| VSWR, Return Loss                 | VSWR (dB) | DC TO 6GHz VSWR 1.13 (24.29) |
| Insertion Loss, dB (Max)          | dB        | 0.05                         |
| 3rd Order IM Product @ 2x20 Watts | dBc       | < -165                       |

**PACKAGING INFORMATION**

|                  |  |   |
|------------------|--|---|
| Package Quantity |  | 1 |
|------------------|--|---|