

## Coaxial Adapter 7-16 Female - N Female with right angle

37.9 REF. Coaxial Adapter 7-16 Female - N Female with right angle **FEATURES / BENEFITS** SW18.2 Marker SW12.0 Cap Cap 5/8"-24UNEF-2A **External Document Links** Notes **Technical features STRUCTURE Product Line** Coaxial Cable Components **Product Type** Coaxial Adapter **MECHANICAL SPECIFICATIONS** Connector A 7-16 Female Center Contact Connector A Phosphor Bronze, silver plated **Outer Contact Connector A** Brass, Tri metal alloy plated **Connector B** N Female **Center Contact Connector B** Phosphor Bronze, silver plated **Outer Contact Connector B** Brass, Tri metal alloy plated Dielectric PTFE **Sealing class** IP68, connected **ELECTRICAL SPECIFICATIONS** Frequency Range - MHz DC - 6000 DC TO 2 GHz VSWR 1.05 (32.25) **VSWR**, Return Loss VSWR (dB) 2 TO 3 GHz VSWR 1.08 (28.3) 3 TO 6 GHz VSWR 1.12 (24.94) Insertion Loss, dB (Max) dΒ 0.05 3rd Order IM Product @ 2x20 dBc < -163 Watts **TEMPERATURE SPECIFICATIONS Operation Temperature** °C (°F) -40 to 85 (-40 to 185) **PACKAGING INFORMATION Package Quantity** 1

**716F-R-NF** REV : A REV DATE : 30 Jan 2025 **www.rfstechnologies.com**