



OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminum) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment. All RFS Technologies connectors are fully tested for mechanical and electrical compliance to industry specifications.

The 7-16 connector is the most rugged RF connection meeting all requirements even under the most severe environmental conditions.

**FEATURES / BENEFITS**

- Cost effective two-piece design for safe and easy installation
- Compatible with copper and aluminium cable types i.e. one connector for both outer conductor materials eliminates the risk of faulty connector installation and helps to keep inventory down
- Robust mechanical design for low and consistent intermodulation performance i.e. keeps the mobile network performance up reduces the number of dropped calls and avoids revenue losses
- Superior electrical performance for consistent and repeatable VSWR i.e. ensure network system performance
- Waterproof to IP 68 i.e. no downtime risk, secures revenue
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



OMNI FIT™ Standard Connectors

**Technical features**

**GENERAL SPECIFICATIONS**

<b>Transmission Line Type</b>	Coaxial Cable		
<b>Cable Size</b>	1 1/4		
<b>Cable Type</b>	Foam Dielectric	Ultraflexible	Radiating
<b>Model Series</b>	UCF114-50A-Series	LCF114-50A-Series	LCFS114-50A-Series
<b>Connector Interface</b>	7-16 DIN		
<b>Connector Type</b>	OMNI FIT™ Standard		
<b>Sealing Method</b>	O-ring		
<b>Gender</b>	Male		

**ELECTRICAL SPECIFICATIONS**

<b>Nominal Impedance, ohms</b>	Ohm	50
<b>3rd Order IM Product @ 2x20 Watts</b>	dBc	-159 typical
<b>Maximum Frequency</b>	GHz	3.6
<b>VSWR, Return Loss</b>	VSWR (dB)	0 &lt; f ≤ 1.0 GHz: 1.03 (36.6) 1.0 &lt; f ≤ 2.7 GHz: 1.05 (32.3) 2.7 &lt; f ≤ 3.6 GHz: 1.08 (28.3)

**MECHANICAL SPECIFICATIONS**

<b>Plating Outer/Inner</b>	Trimetal/Silver	
<b>Length</b>	mm (in)	69.3 (2.7)
<b>Outer Diameter</b>	mm (in)	48.8 (1.9)
<b>Inner Contact Attachment</b>	Spring Finger	
<b>Outer Contact Attachment</b>	Spring C-Ring	



### 716M-LCF114-C02


7-16 DIN Male Connector for 1-1/4" Coaxial Cable, OMNI FIT™ standard, O-ring sealing

#### ACCESSORIES

<b>Wrench size front</b>	mm (in)	Open end wrench 45 (1-3/4)
<b>Wrench size rear</b>	mm (in)	Open end wrench 45 (1-3/4)
<b>Poly Hook Spanner</b>	mm (in)	PHS 60-90-5 Ø 60-90 (2.3-3.5) Pin 5 (0.2)

#### TESTING AND ENVIRONMENTAL

<b>Waterproof Level</b>		IP68
-------------------------	--	------



- [External Document Links](#)
- [Application Note](#)
- [Installation Instruction](#)

[Notes](#)