

# 7-16 DIN Male Connector for 3/8" Coaxial Cable, RAPID FIT™ O-ring sealing

Radio Frequency Systems line of high performance coaxial cable connectors are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up the attachment of connectors to CELLFLEX® coaxial cables. RFS Technologies connectors are fully tested for mechanical and electrical compliance specifications. They are available in all popular cable sizes in a variety of mating interfaces.; The 7-16 connector is the most rugged RF connection meeting all requirements even under severe environmental conditions.

#### FEATURES / BENEFITS

- Single-piece design for Fast and Easy Installation Reliable and simple attachment avoids unnecessary connector adjustments and provides outstanding performance every time. Saves time and provides cost savings.
- Robust Mechanical Design Low and consistent intermodulation performance guarantees outstanding system sensitivity.
- Excellent Electrical Performance Consistent and repeatable low VSWR improves overall system performance and margin and reduces mismatch losses
- Totally Waterproof according to IP 68 Assures safe, long term operation in the harshest of environments.



RAPIT FIT™ Connectors

## **Technical features**

#### **GENERAL SPECIFICATIONS**

Transmission Line Type	Coaxial Cable
Cable Size	3/8
Cable Type	Foam Dielectric
Connector Interface	7-16 DIN
Connector Type	RAPID FIT™
Sealing Method	O-ring
Gender	Male

#### **ELECTRICAL SPECIFICATIONS**

Nominal Impedance, ohms	Ohm	50
3rd Order IM Product @ 2x20 Watts	dBc	-156
Maximum Frequency	GHz	3.7
VSWR, Return Loss	VSWR (dB)	0 < f ≤ 1.0 GHz: 1.02 (40) 1.0 < f ≤ 2.7 GHz: 1.03 (36.6) 2.7 < f ≤ 3.7 GHz: 1.06 (30.7)

### **MECHANICAL SPECIFICATIONS**

Plating Outer/Inner		Silver/Silver
Length	mm (in)	55 (2.2)
Outer Diameter	mm (in)	37 (1.5)
Inner Contact Attachment		Basket
Outer Contact Attachment		Spring Finger


716M-LCF38-070 REV : B REV DATE : 12 Nov 2009 www.rfstechnologies.com



# 7-16 DIN Male Connector for 3/8" Coaxial Cable, RAPID FIT™ O-ring sealing

ACCESSORIES		
Wrench size front	mm (in)	17 (11/16)
Wrench size rear	mm (in)	15 (9/16)
Trimming Tool		TRIM-Series-A
TESTING AND ENVIRONMENTAL		

**Waterproof Level** IP68



**External Document Links** Installation Instruction

Notes

www.rfstechnologies.com REV:B REV DATE: 12 Nov 2009 716M-LCF38-070