



# ANGLE-U-PIM

## Universal Snap-in Adapter, PIM Free Polymer, Angle and Round Member Mounted, Kit 10

The PIM-free universal snap-in adaptor is one of the key components in RFS Technologies' PIM mitigation solutions, which encompass a range of innovative and tested accessories designed to minimize or eliminate external Passive Intermodulation (PIM) at telecommunication sites. Constructed from engineered plastic, this snap-in adaptor effectively prevents PIM caused by metal contacts while securely holding the snap-in hangers in place. Its universal design enables installation on angle members with the provided bolt, as well as on round members using a separately ordered round member adaptor.



### FEATURES / BENEFITS

- Effectively substitute the metal hanger adaptor to reduce PIM effects
- Advanced material and optimal design guarantee the mechanical robustness of the product
- 2 x 3/4" thru holes accommodate a variety of snap style hangers
- A torque stop set bolt ensures proper attachment force
- Maximum loading: 3 polymer hangers or two metal hangers

## Technical features

### STRUCTURE

<b>Product Line</b>		PIM Mitigation		
<b>Product Type</b>		Installation Hardware		
<b>Installation Hardware Type</b>		Snap-in Hanger Adaptor		
<b>Coaxial Cable Type</b>		Coax Cables	Hybrid Cables	Elliptical Waveguides
<b>Configuration</b>		It has a torque stop screw which has two heads. The top head will snap off when correct tightening torque is achieved. The bottom head will remain to enable adaptor removal.		

### MECHANICAL SPECIFICATIONS

<b>Insert Holes</b>		2x 3/4" (19mm) holes		
<b>Color</b>		Black		
<b>Material</b>		Engineered Plastic		

### TEMPERATURE SPECIFICATIONS

<b>Operation Temperature</b>	°C (°F)	-20 to 85 (-4 to 185)		
------------------------------	---------	-----------------------	--	--

### PACKAGING INFORMATION

<b>Package Quantity</b>		10		
<b>Weight per kit</b>	kg (lb)	0.48 (1.06)		

#### External Document Links

[Installation Instruction](#)

#### Notes