



### C137-060TG

Connector for FLEXWELL® elliptical waveguide E60/EP60, CPR137G Flange, Tunable

Tunable connector for FLEXWELL® elliptical waveguide E60 with CPR137G flange, gasket sealed frequency range: 5.925 - 6.425 GHz

[FEATURES / BENEFITS](#)

#### Superior Design


- Fewer tuning screws
- Better performance

#### Quick & Easy Installation

- Flaring tools not required
- Assemble using standard hand tools performance

#### Assorted Connector Types

- Standard (non-tunable), tunable and pre-tuned versions are available
- Two basic interface series - flange can mate with either a choke or a cover flange



C61-137ET Tunable

## Technical features

### STRUCTURE

<b>Transmission Line Type</b>		Elliptical Waveguide	
<b>Cable Type</b>		E60	EP60
<b>Model Series</b>		E60 Series	EP60 Seires
<b>Connector Frequency Range</b>	GHz	5.925 - 6.425	
<b>Connector Type</b>		Tunable	
<b>Sealing Method</b>		Gasket	
<b>Gas Inlet</b>		NPT 1/8, gas adaptor not included	
<b>Connector Interface</b>		CPR137G	

### MECHANICAL SPECIFICATIONS

<b>Length</b>	mm (in)	132 (5.2)
<b>Outer Diameter</b>	mm (in)	74 (2.9)
<b>Weight</b>	kg (lb)	1.54 (3.4)

[External Document Links](#)  
[Installation Instruction](#)

Notes