



CLAMP-105

Cable hanger, non-insulated, bolt-on, for 7/8" coaxial cable and E100, E105 elliptical waveguide

Hanger, non-insulated, bolt-on for coaxial cable
LCF78 / UCF78 / RCF78 / HCA78
and for elliptical waveguide EP100/E105/EP105
made of stainless steel

FEATURES / BENEFITS

Stainless steel hangers for supporting elliptical waveguide to tower. Recommended spacing 1m (3 feet). Hanger may be attached to angle adapters, tower standoffs, member mounting holes with up to M10 or 3/8"-16 hardware or to round member adapters through slot



Technical features

GENERAL SPECIFICATIONS

| | | |
|-------------------------------|--|--|
| Product Line | | Coaxial Cable Accessories Radiating Cable Accessories Elliptical Waveguide Accessories Hybrid Cable Accessories |
| Product Type | | Hanger |
| Hanger Type | | Bolt-On, non-insulated |
| Transmission Line Type | | LCF78 UCF78 RCF78 EP100 E105 EP105 HB078 HCA78 |
| Cable Type | | Coaxial Foam Dielectric Radiating Cable Hybrid |

MECHANICAL SPECIFICATIONS

| | | |
|---|--|-----------------|
| Cable Size | | 7/8 |
| Number of Cable / Waveguide Runs | | 1 |
| Material | | Stainless Steel |

TEMPERATURE SPECIFICATIONS

| | | |
|------------------------------|---------|-------------------------|
| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| Storage Temperature | °C (°F) | -50 to 85 (-58 to 185) |

PACKAGING INFORMATION

| | | |
|-------------------------|--|----|
| Package Quantity | | 10 |
|-------------------------|--|----|

External Document Links

Notes