

## Universal clamp with clamp lining for FLEXWELL® Elliptical Waveguide E60

The set consists of a hot dip galvanized universal clamp and a rubber clamp lining for FLEXWELL  $^{\otimes}$  Elliptical Waveguide E60

## **FEATURES / BENEFITS**

## Easy waveguide installation

- The universal clamp with clamp lining is used for proper and secure installation of elliptical waveguides
- · A suitable rubber inlet is included



## **Technical features**

| GENERAL SPECIFICATIONS              |         |  |
|-------------------------------------|---------|--|
| Product Line                        |         | Elliptical Waveguide Accessories                             |
| Product Type                        |         | Hanger   |
| Hanger Type                         |         | Basic clamp with clamp lining                                |
| Transmission Line Type              |         | E60<br>EP60  |
| MECHANICAL SPECIFICATIONS           |         |  |
| Number of Cable / Waveguide<br>Runs |         | 1  |
| Material                            |         | Clamp: Hot dip galvanized steel<br>Clamp Lining: EPDM rubber |
| TEMPERATURE SPECIFICATIONS          |         |  |
| Operation Temperature               | °C (°F) | -50 to 85 (-58 to 185 )                                      |
| Storage Temperature                 | °C (°F) | -50 to 85 (-58 to 185 )                                      |
| PACKAGING INFORMATION               |         |  |
| Package Quantity                    |         | 10   |

External Document Links

**Notes** 

CLAMP-R-060 REV : A REV DATE : 01 Dec 2008 www.rfstechnologies.com