

High speed grounding kit for CELLFLEX® LCF 78

This Grounding Kit has been developed by RFS Technologies for the CELLFLEX cable series. The Grounding Kit body facilitates a proper attachment to the coaxial cable, ensuring that the performance of the coaxial cable is not being compromised. The tin plated copper mesh provides a secure, low resistance contact to the cable outer conductor. The installation only takes a few minutes. No additional sealing with mastic and electrical tape required.

FEATURES / BENEFITS

- Compatible with both copper and aluminium cable types i.e. one Grounding Kit for both outer conductor materials eliminates the risk of faulty Grounding Kit installation and helps to keep inventory down.
- This kit has been verified by independent labs to withstand the damaging effects of lightning current in excess of 100kA 8/20µs. The copper wire provides the most practical and effective low inductance transfer of lightning induced current to ground.
- No influence on the electrical transmission characteristics of the coaxial cable.
- Robust mechanical design.
- UV resistant according to DIN EN ISO 4892-2 (Plastics Methods of exposure to laboratory light sources Part 2 Xenon-arc-lamps).
- Ozone resistant according to DIN 53509 (Testing of rubber Determination of resistance to ozone cracking).
- Compliant to RoHS (EU 2002/95/EC) and CRoHS (China SJ/T11363-2006) i.e. usable on a global basis.



GKSPEED20-78P shown

Technical features

STRUCTURE

Product Line	Coaxial Cable Accessories Hybrid Cable Accessories
Type of Grounding Kit	High Speed
Transmission Line Type	LCF78, UCF78, HB078
Cable Type	Coaxial Foam Dielectric, Hybrid
Cable Size	7/8"
Number of Cable / Waveguide Runs	1
Material	Grounding Kit Body: Stainless steel, with vulcanised EPDM (Ethylene-Propylene-Caoutchouc) Screws: Stainless steel with safety washers Contact element: Tin-plated copper mesh

ACCESSORIES

Recommended Tool	JSTRIP-78-2

GKSPEED20-78P REV : G REV DATE : 01 Feb 2024 www.rfstechnologies.com



High speed grounding kit for CELLFLEX[®] LCF 78

MECHANICAL SPECIFICATIONS

Lug Attachment Method		Factory Attached
Lug Style Size		1-hole Ø 10.2mm (13/32") crimp-on, tin-plated
Grounding Wire Length	m (in)	0.5 (20)
Grounding Wire Size	mm²	16mm ² (7x7 strand)
Grounding Wire Color		Black
Grounding Body Color		Black
Sealing Class		IP68

TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)

PACKAGING INFORMATION

Package Quantity		1
Weight per piece	kg (lb)	0.3 (0.66)



GKSPEED20-78P

External Document Links Installation Instruction

Notes

Datasheet also applies to GKSPEED20-78GRP (grey), GKSPEED20YG-78P (yellow/green) except for grounding wire color

GKSPEED20-78P REV : G REV DATE : 01 Feb 2024 www.rfstechnologies.com