



HA-DCPLUG-LI-xx Series

HYBRIFLEX® DC Connector Splitter for Low Inductance, Concentric Power Wire Kit

RFS' patented DC wire insulator. Specially designed for Low Inductance, coaxial/concentric, DC wire installation in junction boxes and other applications. Allows for constant and safe termination of these special wire types in various types of terminal block connectors.

FEATURES / BENEFITS

- Avoids short circuits when using Low Inductance wire
- Made of flexible material for easier installation
- Included with many of the the "LI" type HYBRIFLEX cables from RFS
- Also offered separately in muti-piece kits



[External Document Links](#)
[Installation Guidelines](#)

[Notes](#)

Technical features

GENERAL SPECIFICATIONS

| | | |
|---------------------|--|-------------------------------|
| Product Type | | Power Wire Splitter Connector |
|---------------------|--|-------------------------------|

MECHANICAL SPECIFICATIONS

| | | |
|---|---------|---|
| Material | | PVC |
| Weight | kg (lb) | 0.003 (0.007) |
| Dimensions Power Connector (LxWxD) | mm (in) | 13.6 x 15.4 x 51.9 (0.54 x 0.61 x 2.04) |

TESTING AND ENVIRONMENTAL

| | | |
|---------------------------------|---------|-------------------------|
| Storage Temperature | °C (°F) | -40 to 75 (-40 to 167) |
| Operation Temperature | °C (°F) | -40 to 75 (-40 to 167) |
| Installation Temperature | °C (°F) | -40 to 75 (-40 to 167) |
| UV-Protection | | Yes |

ELECTRICAL SPECIFICATIONS

| | | |
|-------------------------------------|--|-------|
| Supported Wire Cross Section | | 6 AWG |
|-------------------------------------|--|-------|

ADDITIONAL INFORMATION

| | | |
|------------------|--|--------------------------|
| Kit Model | | Quantity Provided in Kit |
| HA-DCPLUG-LI-06 | | 6 |
| HA-DCPLUG-LI-14 | | 14 |



PRODUCT DATASHEET

HA-DCPLUG-LI-xx Series

HYBRIFLEX® DC Connector Splitter for Low Inductance, Concentric Power Wire Kit

