



**HA-FODC-LLBB-21-XX**

HYBRIFLEX™; Hybrid jumper cable, Single-mode fibre, 6 mm<sup>2</sup> Power cable, Box to Radio Module; with LC Duplex Connectors;

**RFS' HYBRIFLEX™** cabling solution for Remote Radio Head (RRH) combines optical fibre and DC power for RRHs in a single lightweight aluminum corrugated cable, making it the world's most innovative solution for RRH deployments. It was developed to reduce installation complexity and cost at cellular sites.

**HYBRIFLEX™** cabling solutions allows mobile operators deploying RRH architecture to standardize RRH installation process and eliminates the need for and the cost of cable grounding.

The **HYBRIFLEX™** jumper is part of the cabling solution for RRH's. It consists of an armored part of length XX, a breakout part to the RRH and a breakout part to the distribution box. The breakout part to the RRH is outdoor ready and sealed according to IP68.

The jumper cables can be ordered in 1m - 20 m armored length in 1 m incremental.



**FEATURES / BENEFITS**

- **Aluminum corrugated armor with outstanding bending characteristics**

Minimizes installation time and enables mechanical protection and shielding

- **Built in animal protection**

Improves the reliability of the installation

- **Outer conductor grounding**

Eliminates typical grounding requirement and saves on installation costs

- **Lightweight solution and compact design**

Decreases tower loads

- **Optical fibre and power cables housed in single corrugated cable**

Saves CAPEX by standardizing RRH cable installation and reducing installation equipments

- **Outdoor polyethylene jacket**

Ensure long-lasting cable protection

**Technical features**

**STRUCTURE**

Cable Type		Hybrid jumper
------------	--	---------------

**DC POWER CABLE SPECIFICATIONS**

Number of DC Pairs		1
Maximum DC-Resistance Power Cable	Ω/km (Ω/kft)	3.3 (1.51)
Cross Section of Power Cable	mm <sup>2</sup> (AWG)	6 ( )
Shielding		Provided by Al armor
DC Wire Jacket Material		Polyethylene grey / blue (colours will change to comply with British Standards)
DC Wire Jacket Thickness	mm (in)	0.5 (0.02)
DC Cable Jacket		UV stable black PE
DC Standards (Meets or Exceeds)		IEC 60228
Current Rating		42 (ambient 35°C)
Power Termination End 1		Only barewire without ferrule
Power Termination End 2		With ferrule for box connection

**HA-FODC-LLBB-21-XX**

HYBRIFLEX™; Hybrid jumper cable, Single-mode fibre, 6 mm<sup>2</sup> Power cable, Box to Radio Module; with LC Duplex Connectors;

**MECHANICAL SPECIFICATIONS**

<b>Cable Weight</b>	kg/m (lb/ft)	0.235 (0.158)
<b>Minimum Bending Radius, (Operating)</b>	mm (in)	70 (2.7)
<b>Minimum Bending Radius, (Installation)</b>	mm (in)	125 (5)
<b>Tensile Strength</b>	N (lb)	150 (33.7)

**CABLE JACKET**

<b>UV-Protection Individual and External Jacket</b>		External Jacket: to IEC 60754-1/-2, Inner Jacket, DC conductors + Fibre cables EN 50289-4-17:2015
<b>Jacket Material</b>		UV stable black PE CPR class F + ISO 14001:2015 RoHS 2011/65/EU - China RoHS SJ/T 11364-2006 REACH (EC 1907/2006) UL1581 - UV Resistance Jacket
<b>Outer Diameter Nominal</b>	mm (in)	15.8 (0.622)

**ARMOR SPECIFICATIONS**

<b>Armor Type</b>		Corrugated aluminum
<b>Maximum DC-Resistance of Armor</b>	Ω/km (Ω/kft)	2.42 (0.74)
<b>Copper Equivalent Cross Section of Armor</b>	mm <sup>2</sup> (AWG)	8.45 ( )
<b>Diameter Corrugated Armor</b>	mm (in)	13.8 (0.543)

**F/O CABLE SPECIFICATIONS**

<b>F/O Cable Type</b>		Tight buffer, G657A2 Single-mode
<b>Number of F/O Pairs</b>		2
<b>Core/Clad</b>	μm	9 /125
<b>Secondary Protection Nominal</b>	μm (in)	900 (0.036)
<b>Optical Loss</b>	dB/Km	0.4 @ 1310 nm 0.25 @ 1550 nm
<b>Fiber Termination End 1</b>		Duplex LC Connector
<b>Fiber Termination End 2</b>		Duplex LC Connector

**TESTING AND ENVIRONMENTAL**

<b>Storage Temperature</b>	°C (°F)	-40 to 85 (-40 to 185 )
<b>Operation Temperature</b>	°C (°F)	-40 to 85 (-40 to 185 )
<b>Installation Temperature</b>	°C (°F)	-20 to 50 (-4 to 122 )

**ADDITIONAL ASSEMBLIES**

<b>Length</b>		Model name
<b>2 m</b>		HA-FODC-LLBB-21-02
<b>3 m</b>		HA-FODC-LLBB-21-03
<b>5 m</b>		HA-FODC-LLBB-21-05
<b>7 m</b>		HA-FODC-LLBB-21-07
<b>10 m</b>		HA-FODC-LLBB-21-10



**HA-FODC-LLBB-21-XX**

HYBRIFLEX™;Hybrid jumper cable, Single-mode fibre, 6 mm<sup>2</sup> Power cable, Box to Radio Module; with LC Duplex Connectors;

15 m	HA-FODC-LLBB-21-15
20 m	HA-FODC-LLBB-21-20
	Other length available on request

**RECOMMENDED TOOLS**

<b>Earthing: GKSPEED20-12P</b>	Boots for Nokia RRH: AOPC HA-AOPC-01	Boots for Ericsson RRH: IP-RC HA-FOPLUG-A-04
<b>Clamps: single MBH-12S; double MBH-12D</b>		

[External Document Links](#)

[Notes](#)