

Hangers for the installation of HCA Air Dielectric Cable cables on different supporting profiles. Cable Clamp and Extended Counterbed hot-galvanized steel Screw: stainless steel.

FEATURES / BENEFITS



picture shows the 1L4 version for illustration purpose only

Technical features

| GENERAL SPECIFICATIONS | | |
|--|---------|--|
| Product Line | | Coaxial Cable Accessories |
| Product Type | | Hanger |
| Hanger Type | | Flat iron 6-12mm (0.24-0.47") |
| Transmission Line Type | | HCA300 |
| Cable Type | | Air Dielectric |
| MECHANICAL SPECIFICATIONS | | |
| Cable Size | | 3 |
| Material | | Cable Clamp : hot-dip galvanized Extended Counterbed : hot-dip galvanized Screw: Stainless steel |
| Recommended / Maximum Clamp Spacing | m (ft) | 0.8 / 1.2 (2.75 / 4) |
| TEMPERATURE SPECIFICATIONS | | |
| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| Storage Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| PACKAGING INFORMATION | | |
| Package Quantity | | 1 |
| Weight per piece | kg (lb) | 0.48 (1.05) |

External Document Links

Notes

Hangers for flat iron 6-12 mm (0.24-0.47")

HCH-300-1R

REV DATE : 27 May 2024

www.rfstechnologies.com