



**KRTS2-A**

Tower Stand-off Kit 25-51 mm (1-2") Diameter, 3/8" Hardware

Stainless steel standoff adapter with 3/8" thread  
 Stainless steel round member adapter 25-51mm (1-2in)

**FEATURES / BENEFITS**

- Constructed of heavy stainless steel
- The stand-offs provide 1-1/4" (30 mm) tower clearance to hangers when running waveguide over tower cross members, flanges and other tower obstacles.
- The kit consists of ten stainless steel tower stand-offs with stainless steel hardware.
- Use with Threaded Rod Kit for additional tower clearance.



Stand-off Kit KRTS2-A

**Technical features**

**STRUCTURE**

Product Line		Elliptical Waveguide Accessories Coaxial Cable Accessories	
Product Type		Installation Hardware	
Installation Hardware Type		Round Member Tower Stand-off Kit	
Coaxial Cable Type		Air Dielectric	Foam Dielectric
Configuration		25-51mm (1-2") Diameter, 3/8" Hardware	

**MECHANICAL SPECIFICATIONS**

Tower Member Diameter	mm (in)	25 - 51 (1 - 2 )
Material		Stainless Steel

**TEMPERATURE SPECIFICATIONS**

Installation Temperature	°C (°F)	-50 to 85 (-58 to 185 )
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185 )
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185 )

**PACKAGING INFORMATION**

Package Quantity		10
------------------	--	----

[External Document Links](#)

[Notes](#)