

Tower Stand-off Kit 51-76mm (2-3") Diameter, 3/8" Hardware

Stainless steel standoff adapter with 3/8" thread Stainless steel round member adapter 51-76mm (2-3in) FEATURES / BENEFITS

•Constructed of heavy stainless steel

- •The stand-offs provide 1-1/4" (30 mm) tower clearance to hangers when running waveguide over tower cross members, flanges and other tower obstacles.
- •The kit consists of ten stainless steel tower stand-offs with stainless steel hardware.
- •Use with Threaded Rod Kit for additional tower clearance.



Stand-off Kit KRTS2-B

Technical features

STRUCTURE

Product Line		Elliptical Waveguide Accessories Coaxial Cable Accessories	
Product Type	Instal	Installation Hardware	
Installation Hardware Type	Round Mem	Round Member Tower Stand-off Kit	
Coaxial Cable Type	Air Dielectric	Foam Dielectric	
Configuration	51-76mm (2-3")	51-76mm (2-3") Diameter, 3/8" Hardware	

MECHANICAL SPECIFICATIONS

Tower Member Diameter	mm (in)	51 - 76 (2 - 3)
Material		Stainless Steel

TEMPERATURE SPECIFICATIONS

Installation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)

PACKAGING INFORMATION

П	TACING IN CHILATON					
	Package Quantity			10		

External Document Links

Notes

KRTS2-B REV : C REV DATE : 25 Apr 2013 www.rfstechnologies.com