



### KRTS2-C

## Tower Stand-off Kit 76-102mm (3-4") Diameter, 3/8" Hardware

Stainless steel standoff adapter with 3/8" thread  
Stainless steel round member adapter 76-102mm (3-4in)

#### FEATURES / BENEFITS

- Constructed of heavy stainless steel
- The stand-offs provide 1-1/4" (30 mm) tower clearance to hangers when running waveguide over tower cross members, flanges and other tower obstacles.
- The kit consists of ten stainless steel tower stand-offs with stainless steel hardware.
- Use with Threaded Rod Kit for additional tower clearance.



Stand-off Kit KRTS2-C

## Technical features

### STRUCTURE

Product Line		Elliptical Waveguide Accessories Coaxial Cable Accessories	
Product Type		Installation Hardware	
Installation Hardware Type		Round Member Tower Stand-off Kit	
Coaxial Cable Type		Air Dielectric	Foam Dielectric
Configuration		76-102mm (3-4") Diameter, 3/8" Hardware	

### MECHANICAL SPECIFICATIONS

Tower Member Diameter	mm (in)	76 - 102 (3 - 4 )
Material		Stainless Steel

### TEMPERATURE SPECIFICATIONS

Installation Temperature	°C (°F)	-50 to 85 (-58 to 185 )
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185 )
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185 )

### PACKAGING INFORMATION

Package Quantity		10
------------------	--	----

[External Document Links](#)

[Notes](#)