

Double Multi-block hanger one layer, with angle member adapter

Double Multi block hanger support systems are designed for organizing bundled runs of coax cable. Each space-saving block securely holds two runs of coax, allowing a compact bundle of up to 6x runs to be supported by stacking three blocks.

FEATURES / BENEFITS



MBH114-2-F for illustration purpose

Technical features

Color

GENERAL SPECIFICATIONS	
Product Line	Coaxial Cable Accessories
Product Type	Hanger
Hanger Type	Single Multi-block
Transmission Line Type	LCF12

Black

MECHANICAL SPECIFICATIONS

Cable Size		1/2
Number of Cable / Waveguide Runs		2 per layer, 1 layer, 2 run
Configuration		incl. Angle member adapter
Angle member adapter clamping range mm (in)		4 / 24 (0.157 / 0.945)
Angle member adpter threads		2x M8
Material		Metal parts: -Connecting devices:Stainless steel -Angle member adapter: Stainless steel -Plastic parts: Polypropylene
Length	mm (in)	130 (5.12)
Height	mm (in)	58 (2.28)
Width	mm (in)	50 (1.96)
Recommended / Maximum Clamp Spacing	m (ft)	0.6 / 1 (2 / 3.25)

TEMPERATURE SPECIFICATIONS

Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)

MBH12-2-F REV : D REV DATE : 27 Sep 2022 www.rfstechnologies.com



Double Multi-block hanger one layer, with angle member adapter

PACKAGING INFORMATION

Package Quantity		10
Weight per piece	kg (lb)	0.173 (0.38)
Weight per kit	kg (lb)	1.75 (3.8)



picture shows MBH114-6-F for illustration purpose

External Document Links

Installation Instruction

Notes

www.rfstechnologies.com REV: D REV DATE: 27 Sep 2022 MBH12-2-F