

Double Multi block hanger support systems are designed for organizing bundled runs of coax cable. Each space-saving block securely holds two runs of coax, allowing a compact bundle of up to 6x runs to be supported by stacking three blocks.

FEATURES / BENEFITS

MBH114-6-F for illustration purpose

Technical features

Product Line		Coaxial Cable Accessories
Product Type		Hanger
Hanger Type		Single Multi-block
Transmission Line Type		LCF12 HCA12-50
Color		Black
MECHANICAL SPECIFICATIONS		
Cable Size		1/2
Number of Cable / Waveguide Runs		2 per layer, 3 layer, 6 runs
Configuration		incl. Angle member adapter
Angle member adapter clamping range mm (in)		4 / 24 (0.157 / 0.945)
Angle member adpter threads		2x M8
Material		Metal parts: -Connecting devices:Stainless steel -Angle member adapter: Stainless steel -Plastic parts: Polypropylene
Length	mm (in)	190 (7.48)
Height	mm (in)	58 (2.28)
Width	mm (in)	50 (1.96)
Recommended / Maximum Clamp Spacing	m (ft)	0.6 / 1 (2 / 3.25)
TEMPERATURE SPECIFICATIONS		
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)
PACKAGING INFORMATION		
Package Quantity		10
Weight per piece	kg (lb)	0.263 (0.58)
Weight per kit	kg (lb)	2.65 (5.8)

MBH12-6-F

REV DATE : 27 Sep 2022

www.rfstechnologies.com





External Document Links Installation Instruction Notes