



Single block hanger support systems are designed for organizing bundled runs of coax cable and trunk cable.

Each space-saving block securely holds two runs of cables, allowing a compact bundle of up to 3x runs to be supported by stacking three blocks.

**FEATURES / BENEFITS**

**Multi Blocks are manufactured of polypropylene providing thermal, chemical and UV resistance in all environments.**

They come including angle member adapter and necessary hardware.

**The angle member adapter fastens the clamp to the tower without drilling.**

The angle member adapter includes a tower member set screw.

**The hanger mounting rod may be located in either of two mounting holes, depending on orientation of the fixing member.**

**Compliant to RoHS (EU 2002/95/EC) and CRoHS (China SJ/T11363-2006) i.e. usable on a global basis.**



**Technical features**

**GENERAL SPECIFICATIONS**

Product Line		Hybrid Cable Accessories
Product Type		Hanger
Hanger Type		Single-block
Transmission Line Type		F/O cable fixation LCF12 clamp with rubber inlet
Color		Black

**MECHANICAL SPECIFICATIONS**

Cable Size		1/2
Number of Cable / Waveguide Runs		3 layers, 3 runs
Configuration		Incl. Angle member adapter
Material		Metal parts: -Connecting devices:Stainless steel -Angle member adapter: Stainless steel -Plastic parts: Polypropylene
Length	mm (in)	162 (6.38)
Height	mm (in)	50 (1.96)
Width	mm (in)	50 (1.96)
Recommended / Maximum Clamp Spacing	m (ft)	1 / 1.2 (3.25 / 4)

**TEMPERATURE SPECIFICATIONS**

Operation Temperature	°C (°F)	-40 to 85 (-58 to 185 )
Storage Temperature	°C (°F)	-40 to 85 (-58 to 185 )

**PACKAGING INFORMATION**

Weight per piece	kg (lb)	0.18 (0.4)
------------------	---------	------------



**MBHT07-3-F**

Single-block hanger with three layer, with angle member adapter

**External Document Links**

**Notes**