

Coaxial Adapter N Female - N Female with right angle

Coaxial Adapter N Female - N Female with right angle 30. OREF. **FEATURES / BENEFITS** Marker OREF. Cap 5/8"-24UNEF-2A **External Document Links** Notes **Technical features** STRUCTURE **Product Line** Coaxial Cable Components **Product Type** Coaxial Adapter **MECHANICAL SPECIFICATIONS Connector A** N Female **Center Contact Connector A** Phosphor Bronze, silver plated **Outer Contact Connector A** Brass, Tri metal alloy plated **Connector B** N Female **Center Contact Connector B** Phosphor Bronze, silver plated **Outer Contact Connector B** Bras, Tri metal alloy plated Dielectric PTFE **Sealing class** IP68, connected **ELECTRICAL SPECIFICATIONS** Frequency Range - MHz DC - 6000 DC TO 2 GHz VSWR 1.05 (32.25) **VSWR**, Return Loss VSWR (dB) 2 TO 3 GHz VSWR 1.08 (28.3) 3 TO 6 GHz VSWR 1.12 (24.94) Insertion Loss, dB (Max) dΒ 0.05 3rd Order IM Product @ 2x20 dBc < -163 Watts **TEMPERATURE SPECIFICATIONS Operation Temperature** °C (°F) -40 to 85 (-40 to 185) **PACKAGING INFORMATION Package Quantity** 1

NF-R-NF REV : A REV DATE : 22 Dec 2024 www.rfstechnologies.com