

Elliptical Waveguide to Type N Female Coax Adapter

The high performance coaxial cable to waveguide adapter is specifically designed to provide the highest quality interface while simplifying and speeding up the attachment of connectors to the RADIAFLEX® radiating waveguide RE60. The connector provides outstanding value to users because they permit quick, easy and reliable installation at any location, thereby allowing the operator flexibility while saving installation time.

FEATURES / BENEFITS

- **Waveguide installation** the flange adapter provides proper matching of elliptical waveguide flanges to N-female connector.
- **Time-saving and easy installation** reliable and simple attachment avoids unnecessary connector adjustments and provides outstanding performance. Saves time and provides cost savings.
- Robust mechanical design ideally for in-tunnel applications.
- Excellent electrical performance low VSWR
- Totally waterproof assures safe, long term operation.



NF-RE60

Technical features

GENERAL SPECIFICATIONS

Transmission Line Type	Elliptical Waveguide
Cable Size	RE60
Connector Interface	N female
Connector Type	Axially in the direction of the installed waveguide
Sealing Method	Shrinking Sleeve
Gender	Female

ELECTRICAL SPECIFICATIONS


Nominal Impedance, ohms	Ohm	50
VSWR, Return Loss	VSWR (dB)	5.0 < f ≤ 6.0 GHz: 1.12 (24.9)

MECHANICAL SPECIFICATIONS

Plating Outer/Inner		Brass
Length	mm (in)	75 (2.95)
Outer Diameter	mm (in)	69 (2.72)

TESTING AND ENVIRONMENTAL

Waterproof Level	IP68
------------------	------



External Document Links

NF-RE60 REV : A REV DATE : 07 Sep 2015 www.rfstechnologies.com



Elliptical Waveguide to Type N Female Coax Adapter

Installation Instruction	Notes Power Rating: 10 Watt Earthing: via M6 screw

NF-RE60 REV : A REV DATE : 07 Sep 2015 www.rfstechnologies.com