



Radio Frequency Systems line of high performance coaxial cable connectors are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up the attachment of connectors to Air Dielectric Cable coaxial cables. RFS Technologies connectors are fully tested for mechanical and electrical compliance specifications. They are available in all popular cable sizes in a variety of mating interfaces. The N connector is one of the most common RF connector types. N type connectors from RFS Technologies will be delivered with a non-slotted outer conductor contact sleeve and a special gasket. Due to a special design of the coupling nut (without spring ring) N connectors can be tightened with increased torque. This increases the contact pressure.



Connector N plug CAF

FEATURES / BENEFITS

- Excellent gas tightness, Overpressure for increased voltage handling is maintained throughout the system
- Robust Mechanical Design, Superior and consistent performance guarantees outstanding system characteristics.
- Extremely low reflection factor, Outstanding low reflection factor improves overall system performance and margin and reduces mismatch losses
- Totally Waterproof according to IP 68, Assures safe, long term operation in the harshest of environments. System tightness doesn't have to rely on overpressure from dehydration equipment.

Technical features

GENERAL SPECIFICATIONS

Transmission Line Type		Coaxial Cable
Cable Size		7/8
Cable Type		Air Dielectric
Model Series		HCA78-50 Series
Connector Interface		N
Connector Type		RAPID FIT™
Sealing Method		Sealing compound ¹⁾
Gender		Male

MECHANICAL SPECIFICATIONS

Plating Outer/Inner		Silver/Silver
Length	mm (in)	80 (3.15)
Outer Diameter	mm (in)	39.5 (1.55)
Inner Contact Attachment		Spring Finger
Outer Contact Attachment		Threaded

ACCESSORIES

Wrench size front	mm (in)	36 (1-7/16)
Wrench size rear	mm (in)	32 (1-1/4)

TESTING AND ENVIRONMENTAL

Sealing Volume, cm3 (ounces)	cm ³ (ounces)	5 (0.17)
------------------------------	--------------------------	----------

External Document Links
[Installation Instruction](#)

Notes

¹⁾ The sealing compound must be ordered separately.