



**NMR-SCF12-E01**

N Male Connector for 1/2" Coaxial Cable, OMNI FIT™ Premium, Right Angle, threaded gasket and 360° compression sealing

OMNI FIT™ high performance connectors are designed for use with both CELLFLEX® (copper) and CELLFLEX® Lite (aluminium) cables. They are designed specifically to provide the highest quality connector-cable interface while simplifying and speeding up connector attachment.

All RFS Technologies connectors are fully tested for mechanical and electrical compliance to industry specifications.

The N connector meets all technical requirements and covers high frequencies as well as legacy applications. Sealing against outer conductor and jacket by means of threaded gasket and 360° compression fit. Multifunctional, self-lubricating HighTech polymer assembly locks on cable corrugation, avoids electrochemical potential differences and compression-fits to the jacket.

**FEATURES / BENEFITS**

- Ultra high PIM performance i.e. reduced interference leading to high customer satisfaction
- Two-piece design i.e. visual inspection of interlocking leads to improved installation security
- OMNI FIT™ concept i.e. streamlined order management and reduced stock level
- Watertight sealing in mated and unmated condition, i.e. reduced efforts during installation and improved security during operation
- Unique NiTin plating i.e. extreme resistance against corrosion even under hardest climatic and environmental circumstances
- Multi-thread (Tristart) design i.e. simplified and accelerated tightening process
- RoHS (EU) and CRoHS (China) compliant i.e. can be used on a global basis



OMNI FIT™ Premium Connectors

[External Document Links](#)

[Notes](#)

[Installation Instruction](#)

**Technical features**

**GENERAL SPECIFICATIONS**

<b>Transmission Line Type</b>		Coaxial Cable
<b>Cable Size</b>		1/2
<b>Cable Type</b>		Foam Dielectric Superflexible
<b>Model Series</b>		SCF12-50 Series
<b>Connector Interface</b>		N
<b>Connector Type</b>		OMNI FIT™ PREMIUM Right Angle
<b>Sealing Method</b>		Threaded Gasket + 360° Compression
<b>Gender</b>		Male

**ELECTRICAL SPECIFICATIONS**

<b>Nominal Impedance, ohms</b>	Ohm	50
<b>3rd Order IM Product @ 2x20 Watts</b>	dBc	-156 ; typical -162
<b>Maximum Frequency</b>	GHz	6
<b>VSWR, Return Loss</b>	VSWR (dB)	0 &lt; f ≤ 1.0 GHz: 1.03 (36) 1.0 &lt; f ≤ 2.2 GHz: 1.04 (34) 2.2 &lt; f ≤ 2.7 GHz: 1.06 (30) 2.7 &lt; f ≤ 3.8 GHz: 1.13 (24) 3.8 &lt; f ≤ 5.0 GHz: 1.15 (23) 5.0 &lt; f ≤ 6.0 GHz: 1.22 (20)



### NMR-SCF12-E01

N Male Connector for 1/2" Coaxial Cable, OMNI FIT™ Premium,  
Right Angle, threaded gasket and 360° compression sealing

#### MECHANICAL SPECIFICATIONS

Plating Outer/Inner		Tri metal alloy/Silver
Length	mm (in)	64.1 (2.524)
Outer Diameter	mm (in)	29 (1.142)
Inner Contact Attachment		Spring Finger
Outer Contact Attachment		360° clamping

#### ACCESSORIES

Wrench size front	mm (in)	22
Wrench size rear	mm (in)	22

#### TESTING AND ENVIRONMENTAL

Waterproof Level		IP68
------------------	--	------

