



RCF158-50JFNA-NYCT

1-5/8" RADIAFLEX® RCF Cable, A-series, for NYCT

- RADIAFLEX® functions as a distributed antenna to provide communications in tunnels, mines and large building complexes and is the solution for any application in confined areas.
- Slots in the copper outer conductor allow a controlled portion of the internal RF energy to be radiated into the surrounding environment. Conversely, a signal transmitted near the cable will couple into the slots and be carried along the cable length.
- RADIAFLEX® is used for both one-way and two-way communication systems and because of its broadband capability, a single radiating cable can handle multiple communication systems simultaneously.
- This RADIAFLEX® radiating cable utilize a low-loss cellular polyethylene foam dielectric and a corrugated copper outer conductor which offers a combination of remarkable flexibility, high strength and excellent electrical performance.

• MADE IN MERIDEN, CT USA

FEATURES / BENEFITS

- Broadband radiating cable supporting all wireless application between 30 MHz to 2650 MHz
- Ideally suited for application that require low bending radii
- Robust radiating cable operational under all enviromental conditions as e.g. harsh tunnels or mines



RCF cable, A-series

Technical features

GENERAL SPECIFICATIONS

Size		1-5/8
------	--	-------

ELECTRICAL SPECIFICATIONS

Max. Operating Frequency	MHz	2650
Cable Type		RCF
Impedance	Ohm	50 +/- 2
Velocity, percent	%	89
Capacitance	pF/m (pF/ft)	75 (22.9)
Inductance, uH/m (uH/ft)	µH/m (µH/ft)	0.188 (0.057)
DC-resistance inner conductor, ohm/km (ohm/1000ft)	Ω/km (Ω/1000ft)	1.26 (0.38)
DC-resistance outer conductor, ohm/km (ohm/1000ft)	Ω/km (Ω/1000ft)	0.55 (0.17)
Stop bands	MHz	None



MECHANICAL SPECIFICATIONS

Jacket		JFN
Jacket Color		Standard Black, other colors on request
Jacket Description		Halogen free, non corrosive, flame retardant, low smoke, polyolefin
Slot Design		Milled (Two-Row)
Inner Conductor Material		Corrugated Copper Tube
Outer Conductor Material		Corrugated Copper Tube
Diameter Inner Conductor	mm (in)	17.6 (0.69)
Diameter Outer Conductor	mm (in)	46.5 (1.83)
Diameter over Jacket Nominal	mm (in)	50.3 (1.98)
Minimum Bending Radius, Single Bend	mm (in)	500 (19.7)
Cable Weight	kg/m (lb/ft)	1.3 (0.87)
Tensile Force	N (lb)	1080 (238)
Indication of Slot Alignment		None
Recommended / Maximum Clamp Spacing	m (ft)	1.2 (4)
Minimum Distance to Wall	mm (in)	50 (2)

TESTING AND ENVIRONMENTAL

Jacket Testing Methods		Test methods for fire behaviour of cable : IEC 60754-1/-2 smoke emission: halogen free, non corrosive IEC 61034 low smoke IEC 60332-1 flame retardant
------------------------	--	--

TEMPERATURE SPECIFICATIONS

Storage Temperature	°C(°F)	-70 to 85 (-94 to 185)
Installation Temperature	°C(°F)	-25 to 60 (-13 to 140)
Operation Temperature	°C(°F)	-40 to 85 (-40 to 185)



ATTENUATION

Frequency, MHz	Longitudinal Loss, dB/100 m (dB/100 ft)	Coupling Loss 50%, dB	Coupling Loss 95%, dB
75	0.59 (0.18)	62	74
150	0.86 (0.26)	70	80
450	1.60 (0.49)	83	93
800	2.25 (0.69)	84	94
870	2.37 (0.72)	82	92
900	2.42 (0.74)	82	92
960	2.51 (0.77)	82	92
1800	3.80 (1.16)	81	91
1900	3.94 (1.20)	80	90
2000	4.08 (1.24)	80	90
2200	4.36 (1.33)	80	90
2400	4.65 (1.42)	80	90
2600	4.92 (1.50)	80	90

External Document Links

Notes

- Coupling loss values are average values of all three spatial orientations (radial, parallel and orthogonal) of dipole antenna.
- As with any radiating cable, the performance in building or tunnel environments may deviate from figures based on free space method.

• Spec Rev F specifically for NYCT:

(*) Coupling Loss and Longitudinal Loss values are nominal values in table above and measured by the free space method according to IEC 61196-4 at 2m (6.6ft) distance.

(**) Longitudinal loss values in table above with a tolerance of +/-5 %

(***) Orthogonal Coupling loss measured by the free space method according to IEC 61196-4 at distance of 6 m (20 ft) below

(Maximum Values - 50% RP)

150MHz: 85 dB | 450 MHz; 88 dB | 900MHz: 89 dB