

RSB Clamp Lining for LCF 14 and SCF 38 cable with d = 11 - 12.5 mm over jacket (usable in combination with RSB-12).

FEATURES / BENEFITS

The clamp lining has been designed to be used in combination with the RSB-Clip RSB-12. The use of the clamp lining in combination with RSB-Clip prevents LCF14-50 and SCF38-50 cables against damage e.g. due to cable movement by wind, therefore a deterioration of the electrical properties is avoided.





Technical features

5B-1438/12	REV : A	REV DATE : 08 Mar 2023	www.rfstechnologies.co
External Document Links		Notes Only usable in combination with RSB-12	
Weight per piece	kg (lb)	0.006 (0.013)	
Package Quantity		1	
PACKAGING INFORMATION			
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)	
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)	
TEMPERATURE SPECIFICATIONS			
-		Anchor bar fixation : RSB-315	
Spare Part / Useful Accessories		Cleat : RSB-310	
ACCESSORIES		RSB-Cleat : RSB-12	
	mm (in)	20 (0.79)	
Height Width	mm (in)	20 (0.79)	
Length	mm (in)	34 (1.34)	
Material		EPDM rubber	
Number of Cable / Waveguide Runs		1	
Cable Size		1/4 and 3/8	
MECHANICAL SPECIFICATIONS			
Cable Type		Coaxial Foam Dielectric	
Transmission Line Type		LCF14 SCF38	
Product Type		Clamp Lining	
Product Line		Coaxial Cable Accessories	