

RSB Clamp Lining for LCF 14 and SCF 38 cable

RSB Clamp Lining for LCF 14 and SCF 38 cable with d = 11 - 12.5 mm over jacket (usable in combination with RSB-12).

FEATURES / BENEFITS

The clamp lining has been designed to be used in combination with the RSB-Clip RSB-12. The use of the clamp lining in combination with RSB-Clip prevents LCF14-50 and SCF38-50 cables against damage e.g. due to cable movement by wind, therefore a deterioration of the electrical properties is avoided.



RSB-38/12

Technical features

| Product Line | Coaxial Cable Accessories |
|------------------------|---------------------------|
| Product Type | Clamp Lining |
| Transmission Line Type | LCF14 SCF38 |
| Cable Type | Coaxial Foam Dielectric |

MECHANICAL SPECIFICATIONS

| Cable Size | | 1/4 and 3/8 | | |
|-------------------------------------|---------|-------------|--|--|
| Number of Cable / Waveguide Runs | | 1 | | |
| Material | | EPDM rubber | | |
| Length | mm (in) | 34 (1.34) | | |
| Height | mm (in) | 20 (0.79) | | |
| Width | mm (in) | 20 (0.79) | | |

ACCESSORIES

| | RSB-Cleat : RSB-12 |
|---------------------------------|-------------------------------|
| Spare Part / Useful Accessories | Cleat: RSB-310 |
| | Anchor bar fixation : RSB-315 |

TEMPERATURE SPECIFICATIONS

| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
|-----------------------|---------|-------------------------|
| Storage Temperature | °C (°F) | -50 to 85 (-58 to 185) |

PACKAGING INFORMATION

| Package Quantity | | 1 |
|------------------|---------|---------------|
| Weight per piece | kg (lb) | 0.006 (0.013) |

External Document Links

Notes

Only usable in combination with RSB-12

RSB-1438/12 REV : A REV DATE : 08 Mar 2023 www.rfstechnologies.com