

PRODUCT DATASHEET **RSB-310** RSB Cleat

| Cleat for RSB Clip FEATURES / BENEFITS | | |
|---|---------|---|
| Technical features | | |
| GENERAL SPECIFICATIONS | | |
| Product Line | | Coaxial Cable Accessories Elliptical Waveguide Accessories |
| Product Type | | Hanger |
| Hanger Type | | RSB Cleat |
| Installation Hardware Type | | RSB Cleat |
| Cable Type | | Coaxial Foam Dielectric |
| MECHANICAL SPECIFICATIONS | | |
| Number of Cable / Waveguide Runs | | 1 |
| Angle member adapter clamping range mm (in) | | 1 / 25 (0.039 / 0.9) |
| Angle member adpter threads | | 2x M8 |
| Material | | Cleat: Aluminium Screw: Stainless Steel |
| TEMPERATURE SPECIFICATIONS | | |
| Installation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| Operation Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| Storage Temperature | °C (°F) | -50 to 85 (-58 to 185) |
| PACKAGING INFORMATION | | |
| Package Quantity | | 10 |





External Document Links

Notes

Only usable in combination with RSB-12, RSB-78, RSB-114 & RSB-158.