



RSB Clamp Lining for LCF 38 cable and others with d = 10.5 - 12.5 mm over jacket (usable in combination with RSB-12).

**FEATURES / BENEFITS**

The clamp lining has been designed to be used in combination with the RSB-Clip RSB-12. The use of the clamp lining in combination with RSB-Clip prevents LCF38-50 cables against damage e.g. due to cable movement by wind, therefore a deterioration of the electrical properties is avoided.



RSB-38/12

**Technical features**

**GENERAL SPECIFICATIONS**

<b>Product Line</b>		Coaxial Cable Accessories Hybrid Cable Accessories
<b>Product Type</b>		Clamp Lining
<b>Transmission Line Type</b>		LCF38
<b>Cable Type</b>		Coaxial Foam Dielectric

**MECHANICAL SPECIFICATIONS**

<b>Cable Size</b>		3/8
<b>Number of Cable / Waveguide Runs</b>		1
<b>Material</b>		EPDM rubber
<b>Length</b>	mm (in)	34 (1.34)
<b>Height</b>	mm (in)	20 (0.79)
<b>Width</b>	mm (in)	20 (0.79)

**ACCESSORIES**

<b>Spare Part / Useful Accessories</b>		RSB-Cleat : RSB-12 Cleat : RSB-310 Anchor bar fixation : RSB-315
--	--	--

**TEMPERATURE SPECIFICATIONS**

<b>Operation Temperature</b>	°C (°F)	-50 to 85 (-58 to 185)
<b>Storage Temperature</b>	°C (°F)	-50 to 85 (-58 to 185)

**PACKAGING INFORMATION**

<b>Package Quantity</b>		1
<b>Weight per piece</b>	kg (lb)	0.005 (0.01)

**External Document Links**

**Notes**

Only usable in combination with RSB-12