

Clic Clamp, 1/2" ALF,RCF,RLK polyamide black, halogen free fire class UL94HB

FEATURES / BENEFITS

Safe and efficient installation of RADIAFLEX[®] cable with clic-clamps. Simple mounting by using wall plugs and screws. Simply push in by hand, clamp will grip and lock by applying slight pressure.



Technical features


CENIEDAL	SPECIFICATIONS

GENERAL SPECIFICATIONS		
Product Line		Radiating Cable Accessories
Product Type		Hanger
Hanger Type		SFS clamp
Transmission Line Type		ALFU RLK* RCF12-50*A HCA12-50
Cable Type		Air Dielectric Radiating Cable
Color		Black
MECHANICAL SPECIFICATIONS		
Cable Size		1/2
Number of Cable / Waveguide Runs		1
Material		Polyamide
TESTING AND ENVIRONMENTAL		
Fire Class		UL94 HB
TEMPERATURE SPECIFICATIONS		
Installation Temperature	°C (°F)	-20 to 80 (-4 to 176)
Operation Temperature	°C (°F)	-50 to 85 (-58 to 185)
Storage Temperature	°C (°F)	-50 to 85 (-58 to 185)
PACKAGING INFORMATION		
Package Quantity		150
	_	

SFS-12-01 REV: A REV DATE: 17 Jun 2019 www.rfstechnologies.com



SFS clamp for RADIAFLEX[®] 1/2" (for ALF, RCF RLK)



SFS-12-01 REV : A REV DATE : 17 Jun 2019 www.rfstechnologies.com