



**PRODUCT DESCRIPTION**

RFS Technologies TPS-43 series Tapper/Unequal Divider have been designed for a variety of wireless applications in the frequency band from 350 to 6000MHz. The unit couples off a defined fraction of a RF signal from 5 to 30 dB with minimal reflections or loss. The broad frequency range is ideally suited for multi-band distributed antenna systems or in combination with RADIAFLEX® radiating cables.



**FEATURES / BENEFITS**

- **Broadband 555MHz-6000MHz**
- 4.3-10 Female Interface
- PIM Optimized Design (163dBc @2x43dBm)
- Low Insertion Loss
- High Power Handling
- Small Size, Low Weight

**TECHNICAL FEATURES**

**ELECTRICAL SPECIFICATIONS**

|                                |     |          |
|--------------------------------|-----|----------|
| <b>Frequency Range</b>         | MHz | 350-6000 |
| <b>Power Rating</b>            | W   | 300      |
| <b>Maximum Reflected Power</b> | W   | 200      |
| <b>PIM 3rd @2*43 dBm</b>       | dBc | 163      |
| <b>Input Impedance</b>         | Ohm | 50       |

**MECHANICAL SPECIFICATIONS**

|                          |         |   |
|--------------------------|---------|---|
| <b>Connectors</b>        |         | 4.3-10 Female   |
| <b>Dimensions, L*W*H</b> | mm(in)  | 143.5*46*25<br>(5.65*1.81*0.98)   |
| <b>Net Weight ±10%</b>   | kg (lb) | 0.25(0.55)  |
| <b>Temperature Range</b> | °C      | -25 to +65 (+160 for 2hours in an event of fire, encased in DragonSkin Cabinet) |
| <b>IP Level</b>          |         | IP66  |
| <b>RoHS</b>              |         | Compliant   |



**TPS8-43-350/6000**

Broadband Tapper/Unequal Divider for Wireless & Indoor Application, Support 350-6000MHz with coupling value 8dB

**MODEL NUMBER SPECIFICATIONS**

| Model Number       |    | TPS3-43-350/6000  | TPS5-43-350/6000   | TPS6-43-350/6000  | TPS8-43-350/6000  |
|--------------------|----|---|--|---|---|
| VSWR               |    | 1.25:1@0.698-0.96&1.695-2.7GHz<br>1.35:1@0.35-0.698&3.5-4.5&4.9-6GHz  | 1.25:1@0.35-0.96&1.695-2.7GHz<br>1.3:1@3.5-4.5&4.9-6GHz  | 1.25:1@0.35-0.96&1.695-2.7GHz<br>1.3:1@3.5-4.5&4.9-6GHz   | 1.2:1@0.35-0.96&1.695-2.7GHz<br>1.3:1@3.5-4.5&4.9-6GHz  |
| Coupling Loss      | dB | 3.0   | 5.0  | 6.0   | 8.0   |
| Coupling Tolerance | dB | 4.8dB +0/-1.5dB@0.35-0.38GHz<br>4.8dB +0/-1.3dB@0.38-0.698GHz<br>4.8dB +0/-0.8dB@0.698-0.96GHz<br>4.8dB ±0.8dB@1.695-2.7GHz<br>4.8dB +0/-1.9dB@3.5-4.5GHz<br>4.8dB +0.1/-1dB@4.9-6GHz | 6dB +0/-1.3dB@0.35-0.38GHz<br>6dB +0.2/-1.1dB@0.38-0.698GHz<br>6dB +0.15/-0.45dB@0.698-0.96GHz<br>6dB ±0.6dB@1.695-2.7GHz<br>6dB +0/-1.85dB@3.5-4.5GHz<br>6dB +0.1/-1dB@4.9-6GHz | 7dB +0.3/-1dB@0.35-0.38GHz<br>7dB -0.3/-1dB@0.38-0.698GHz<br>7dB ±0.5dB@0.698-0.96GHz<br>7dB ±0.7@1.695-2.7GHz<br>7dB +0.3/-1.4dB@3.5-4.5GHz<br>7dB ±0.7dB@4.9-6GHz | 8dB+0/-1.3dB@0.35-0.38GHz<br>8dB +0/-0.8dB@0.38-0.698GHz<br>8dB ±0.4dB@0.698-0.96GHz<br>8dB +0.15/-1dB@1.695-2.7GHz<br>8dB +0/-1.5dB@3.5-4.5GHz<br>8dB +0.1/-1.1dB@4.9-6GHz |
| Insertion Loss     | dB | 1.8dB@0.35-0.96GHz<br>2.1dB@1.695-2.7GHz<br>2dB@3.5-4.5&4.9-6GHz  | 1.65   | 1.5   | 1.15  |



**TPS8-43-350/6000**

Broadband Tapper/Unequal Divider for Wireless & Indoor Application, Support 350-6000MHz with coupling value 8dB

**MODEL NUMBER SPECIFICATIONS**

| Model Number       |    | TPS10-43-350/6000  | TPS13-43-350/6000   | TPS15-43-350/6000   | TPS20-43-350/6000  |
|--------------------|----|--|---|---|--|
| VSWR               |    | 1.2:1@0.35-0.96&1.695-2.7GHz<br>1.3:1@3.5-4.5&4.9-6GHz   | 1.2:1@0.35-0.96&1.695-2.7GHz<br>1.3:1dB@3.5-4.5&4.9-6GHz  |   |  |
| Coupling Loss      | dB | 10.0   | 13.0  | 15.0  | 20.0   |
| Coupling Tolerance | dB | 10dB +0/-1.3dB@0.35-0.38GHz<br>10dB +0/-0.8dB@0.38-0.698GHz<br>10dB ±0.45 dB@0.698-0.96GHz<br>10dB ±0.7dB@1.695-2.7GHz<br>10dB +0/-1.5dB@3.5-4.5GHz<br>10dB +0.1/-1.1dB@4.9-6GHz | 13dB ±1.0dB@0.35-0.38GHz<br>13dB ±0.7dB@0.38-0.698GHz<br>13dB ±0.5dB@0.698-0.96GHz<br>13dB ±0.65dB@1.695-2.7GHz<br>13dB +0.25/-1.25dB@3.5-4.5GHz<br>13dB +0.3/-1dB@4.9-6GHz | 15dB ±1.0dB@0.35-0.38GHz<br>15dB ±0.8dB@0.38-0.96GHz<br>15dB ±0.6dB@1.695-2.7GHz<br>15dB +0.3/-1.3dB@3.5-4.5GHz<br>15dB ±0.8dB@4.9-6GHz | 20dB ±1dB@0.35-0.38GHz<br>20dB ±0.8dB@0.38-0.96GHz<br>20dB +0.4/-1.1dB@1.695-2.7GHz<br>20dB +1.2/-0.8dB@3.5-4.5GHz<br>20dB ±1.5dB@4.9-6GHz |
| Insertion Loss     | dB | 0.75   | 0.65  | 0.4   | 0.2dB@0.35-0.96&1.695-2.7GHz<br>0.3dB@3.5-4.5&4.9-6GHz   |

**MODEL NUMBER SPECIFICATIONS**

| Model Number       |    | TPS30-43-350/6000  |
|--------------------|----|--|
| VSWR               |    | 1.2:1@0.35-0.96&1.695-2.7GHz<br>1.3:1dB@3.5-4.5&4.9-6GHz   |
| Coupling Loss      | dB | 30.0   |
| Coupling Tolerance | dB | 30dB+1.7/-0.3dB@0.35-0.698GHz<br>30dB +1.5/-0.2dB@0.698-0.96GHz<br>30dB ±1dB@1.695-2.7GHz<br>30dB +2.7/-0.8dB@3.5-4.5GHz<br>30dB +1.05/-2.5dB@4.9-6GHz |
| Insertion Loss     | dB | 0.2  |

**External Document Links**

[LINK to VEX FILES](#)

**Notes**